



Supplied

D-Ring hangers
Hanging cord



What you'll need

Tape measure
Spirit level
Soft pencil
Screws or picture hooks
(suitable for your wall)
Rawl plugs
(suitable for your wall)
Power drill for
masonry walls
Screwdriver or hammer.

How to install

Hanging your framed print couldn't be easier.
Simply follow our step by step guide.



If you have any questions about installation,
please contact us on 0118 922 1327 or email
info@surfaceview.co.uk for further information
and advice.



1. Offer up the picture frame to the wall and when you are happy with its position mark the centre, top of the frame on the wall with a soft pencil.

2. Next lie the framed art print face down and screw the D-ring hangers into the frame. Then feed the hanging cord through the D-ring hangers and pull taut. Hold towards the top of the frame and measure the distance between the apex of the hanging cord and the top of your frame.

3. Measure this distance down from the mark on the wall. This will give you the desired picture hook position on the wall. Mark it with a pencil.

4. Fix the picture hook or screw in place using a hammer or screwdriver respectively. If your framed art print is large and heavy you will need to first drill a hole in the wall using an appropriate drill and setting. Always use a rawl plug in a masonry wall prior to screwing the fixing in place.

5. Once the wall fixing is in place you can hang your framed art print into place.

If you have any questions about installation, please contact us on 0118 922 1327 or email info@surfaceview.co.uk for further information and advice.